

HDMI 1080P 2, 4 way Splitters

40-1061-1.3-2, 2 Port HDMI Splitter

2 Port

1.3A Compliant



Specifications:

- Video Amplifier Bandwidth: 2.25 GHz · Single Link Range: 1080P/1920 x 1200
- Vertical Frequency Range: 50 - 85 Hz · Wide Frequency Range: 25MHz ~ 225MHz
- HDMI Input/Output Connector: TYPE A 19pin
- Power Consumption: 15 Watts (max.), DC Power 5Vdc, 2A · Dimensions: L - 3.41" x W - 1.85" x H - 1.0" · Weight: .3 lbs.

Features:

- Supports DVI specification 1.0 · Compliant with HDCP Rev 1.2 Specification and HDMI Specification 1.3a · Supports One DVI/HDMI input and 2 HDMI outputs
- Supports conversion of HDMI signals to DVI signals
- Daisy-chainable and Cascadable to make more than 2 outputs
- Allows simultaneous display and outputs are mirrored to two HDMI displays · Supports 480p, 720i, 720p, 1080i and 1080p resolutions with 24/36 bit color depth
- Supports SACD, PCM (7.1), Dolby True HD, DTS-HD Master Audio
- Supports HDCP compliant devices
- Enhances video signals for distance up to 15M
- Supports both Audio and Video signals. · All Steel casing · Ideal for home theater installations, commercial applications, educational facilities.
- L.E.D indicators for signal, Red indicates no active signal, Blue indicates active signal path.

40-1061-1.3-4, 4 Port HDMI Splitter

4 Port

1.3A Compliant



Front



Back

Specifications:

- Video Amplifier Bandwidth: 2.25 GHz · Single Link Range: 1080P/1920 x 1200
- Vertical Frequency Range: 50 - 85 Hz · Wide Frequency Range: 25MHz ~ 225MHz
- HDMI Input/Output Connector: TYPE A 19pin
- Power Consumption: 15 Watts (max.), DC Power 5Vdc, 2A · Dimensions: L - 10.2" x W - 4.5" x H - 1.0" · Weight: 1.85 lbs.

Features:

- Supports DVI specification 1.0 · Compliant with HDCP Rev 1.2 Specification and HDMI Specification 1.3a · Supports One DVI/HDMI input and 4 HDMI outputs
- Supports conversion of HDMI signals to DVI signals
- Daisy-chainable and Cascadable to make more than 4 outputs
- Allows simultaneous display and outputs are mirrored to two HDMI displays · Supports 480p, 720i, 720p, 1080i and 1080p resolutions with 24/36 bit color depth
- Supports SACD, PCM (7.1), Dolby True HD, DTS-HD Master Audio
- Supports HDCP compliant devices
- Enhances video signals for distance up to 15M
- Supports both Audio and Video signals. · All Steel casing · Ideal for home theater installations, commercial applications, educational facilities.
- L.E.D indicators for signal, Red indicates no active signal, Blue indicates active signal path.
- Front panel On/Off switch.

Typical hookup

