


40-1061-1.3-4, 4 Port HDMI Distribution Amplifier

1.3A Compliant



Specifications:


- Video Amplifier Bandwidth: 2.25 GHz · Single Link Range: 1080P/1920 x 1200
- Vertical Frequency Range: 50 - 85 Hz · Wide Frequency Range: 25MHz ~ 225MHz
- HDMI Input/Output Connector: TYPE A 19pin
- Power Consumption: 15 Watts (max.) · Dimensions: 180 x 65 x 25 mm / 3.49" x 2.55" x .984"
- Weight: 280g

Features:

- Supports DVI specification 1.0 · Compliant with HDCP Rev 1.2 Specification and HDMI Specification 1.3a · Supports One DVI/HDMI input and 4 DVI / HDMI outputs
- Supports conversion of HDMI signals to DVI signals
- Daisy-chainable and Cascadable to make more than 4 outputs
- Allows simultaneous display and Outputs are mirrored to four HDMI displays · Supports 480p, 720i, 720p, 1080i and 1080p resolutions with 12 bits color depth
- Supports SACD, PCM (7.1), Dolby True HD, DTS-HD Master Audio
- Supports HDCP compliant devices
- Enhances video signals for distance up to 15M
- Supports BOTH Audio and Video signals. · All Aluminum casing · Ideal for home theater installations, commercial applications, educational facilities.
- LED indicators for signal/power modes.

40-967M, 4 x 2 HDMI Matrix Switcher

1.3A Compliant



Specifications:


- Video Amplifier Bandwidth: 2.25 GHz · Single Link Range: 1080p ~ 1440p 2560 x 1440p
- Deep Color: 12 bits
- Vertical Frequency Range: 50 - 85 Hz · Wide Frequency Range: 25MHz ~ 165MHz
- HDMI Input/Output Connector: TYPE A 19pin
- Power Consumption: 5 Watts (max.) · Dimensions: 180 x 65 x 25 mm / 3.49" x 2.55" x .984"
- Weight: 250 g

Features:

- Supports 4 inputs to 2 single- or dual-link DVI/HDMI (HDMI V-1.3a) outputs.
- Compatible with HDMI V-1.3a or DVI-D, HDCP-enabled HDTVs. · Each port supports HDMI or DVI inputs (both Video and Audio signals).
- Supports high video resolution up to 2560 x 1440 with 12 bit color depth.
- Supports 2.25Gbps signaling rate for 480i/p, 720i/p, 1080i/p and 1440i/p up to 12-bit color depth.
- Supports SACD, PCM (7.1), Dolby True HD, DTS-HD Master Audio
- Supports multiple HD displays for multiple sources, such as HD-DVD players, HDMI enabled PCs or Notebooks, Digital Projectors, PlayStation 3, A/V Receivers and Set Top Boxes.
- Discrete IR Remote Control for operational flexibility, easy control and convenient use.
- Eliminates a hassle for disconnection andreconnection with different sources.
- LED indicators for operation/power modes.

40-992-1.3, 4 x 1 HDMI Switcher

1.3A Compliant



Specifications:

- Video Amplifier Bandwidth: 2.25 GHz · Single Link Range: 1080p ~ 1440p 2560 x 1440p
- Deep Color: 12 bits
- Vertical Frequency Range: 50 - 85 Hz · Wide Frequency Range: 25MHz ~ 165MHz
- HDMI Input/Output Connector: TYPE A 19pin
- Power Consumption: 5 Watts (max.) · Dimensions: 180 x 65 x 25 mm / 3.49" x 2.55" x .984"
- Weight: 250 g

Features:

- Supports 4 inputs to 2 single- or dual-link DVI/HDMI (HDMI V-1.3a) outputs.
- Compatible with HDMI V-1.3a or DVI-D, HDCP-enabled HDTVs. · Each port supports HDMI or DVI inputs (both Video and Audio signals).
- Supports high video resolution up to 2560 x 1440 with 12 bit color depth.
- Supports 2.25Gbps signaling rate for 480i/p, 720i/p, 1080i/p and 1440i/p up to 12-bit color depth.
- Supports SACD, PCM (7.1), Dolby True HD, DTS-HD Master Audio
- Supports multiple HD displays for multiple sources, such as HD-DVD players, HDMI enabled PCs or Notebooks, Digital Projectors, PlayStation 3, A/V Receivers and Set Top Boxes.
- Discrete IR Remote Control for operational flexibility, easy control and convenient use.
- Eliminates a hassle for disconnection andreconnection with different sources.
- LED indicators for operation/power modes.